

PMD Series 15" Industrial Display

Model NO :PMD-150XN-VX



Display Specifications

LCD Display	15" Active Matrix TFT color LCD IP65 Front Panel Protection
Active Display Area	304.128(H) x 228.096(V) mm
Resolution	1024 x 768
Pixels Pitch	0.297 x 0.297 mm
Brightness [cd/m ²]	250 (Typ)
Contrast Ratio	700 : 1(Typ.)
Viewing Angle	170° (H) / 160°(V)

System

I/O Connectors	DC power input x 1 , VGA (15 Pin Female D-SUB) x 1
OSD Control	on the front Side

Power Supply

Power Consumption	30 (watt)
Power Input	DC 12 V

Mechanical

Construction	Aluminum front side and metal housing
Mounting	Panel Mount or VESA Mount (75 x 75 mm)
Dimension	400 x 300 x 41.5 (mm)
Net Weight	3.90 KGS

Environmental

Operating Temperature	0~50°C (32 ~122 °F)
-----------------------	-----------------------


Order Options

Optional DVI Input	Yes
Optional Touch Panel	Resistive (RS232 or USB)



Ordering Information:

- PMD-150XN-VX 15" Industrial Display Aluminmu front bezel and IP65 front side protection
- PMD-150TN-VX 15" Industrial Display Aluminmu front bezel and IP65 front side protection with touch screen

Dimension



UNIT: mm



*Note: This is a simplified drawing and some components are not marked in detail.
 Please contact us for product detail information.