Product Type: AD1210P (100W) (Car Power Board)

**Product Specifications** 

\* Working voltage: DC8V-30V

\* Output voltage: 12V

\* Output current: 8.0A. (10.0A max)

- \* Enter with ACC control (optional)
- \* with a delay of 15 seconds boot (open power board output)
- \* with a delay of 135 seconds off (off the power board output)
- \* with ITPS intelligent control: Acc\_On open 15 seconds delay computer, Acc\_Off delay 30 seconds to remind the computer off
- \* with status indicator function
- \* Super 8bit output with high-speed ADC sampling control output intelligent short circuit protection, short-circuit wire can automatically identify from 0-30 meters short circuit, automatic detection off
- \* The input has reverse polarity protection
- \* Output ripple: <100Mv
- \* Operating temperature:  $-20 \sim 60$  °C
- \* Relative humidity: 5 ~ 95% RH
- \* Safety standards: IEC60950 / IEC60065 / EN50498 / GB4943
- \* Electromagnetic compatibility standards:

EN55022 & EN55024 Class B,

IEC-60068-2-1, IEC-60068-2-2, IEC-61000-4-5 (ISO7637-2), Lever 3,

IEC-61000-4-11, Criteria B,

- \* Dimensions: (L) 102 \* (M) 50 \* (H) 13mm
- \* Weight: 50g