

# Flat Touch monitor

Thin profile , rounded corners , bezel -less



## Features :


- \* 17" VGA 1280 x 1024 LCD panel with LED backlight for power saving and environmental protection
- \* 0°C ~ 50°C range operating temperature
- \* PCAP touchscreen
- \* Multi-touch PCT touchscreen with USB interface
- \* Flexible signal interface: VGA, DVI
- \* VESA mounting
- \* IP65 front panel compliant
- \* True flat surface
- \* 9~36Vdc Power in

Model No :FAD series



## Main Specifications

Display	Model	FAD-170PW-DN
	Size	17" LED Panel
	Resolution	1280 x 1024 ( SXGA)
	Viewing Angle	85° /85° (H), 80° /80° (V)
	Brightness	350 ( cd/m <sup>2</sup> )
	Support color	16.7M colors
	Contrast ratio	1000:1
	Response time	5 msec
Touchscreen	Backlight life( hrs )	30,000 hrs
	Touchscreen type	PCT Multi-touch touchscreen
	Surface Hardness	≥6H
Environment	Transparency	>85%
	Operating Temperature	0 ~ 50°C( 32~122° F)
Mechanical	Storage Temperature	-20~60°C( -4~140° F)
	Construction	Metal chassis with Aluminum profile
	Mounting	VESA mounting
	Dimension	373 x 305 x 39.43 (mm)
System	Net Weight	4.60kgs
	I/O	VGA x 1,DVI x 1 ,USB x 1 for Touch ,phoenix connector x 1 for DC power in
	Power input	9~36Vdc in ,
	Power Consumption	20 Watt
Accessories	EMC compliance	CE/FCC
	VGA cable x 1 , USB cable x 1 , Phoenix male connector x 1	
Optional Items	DVI cable ( 1.5 m )	



\*Note: This is a simplified drawing and some components are not marked in detail. Please contact us for product detail information.