

Product Type: TOSN-LD3200P (80W)

Product Specifications:

- Input voltage: 100~240Vac(Range:90~264Vac).
- Input current: 2A max.
- Input frequency: 50/60Hz(Frequency range:47~63Hz).
- Output voltage: +24V/+12V/+5V/+5VSB
- Output current: 2.0A/2.0A/2.0A/0.5A、 (2.5A/2.0A/3.0A/1.0A max)
- Ripple and noise: 200mV max.
- Operating temperature: -10~45°C
- Relative humidity: 10~90%RH
- Safety standards: UL/EN60950/60065/GB4943
- Electromagnetic compatibility standards:
EN55022 & EN55024 Class B, IEC-61000-4-2,IEC-61000-4-4,Lever 3,
Criteria B,IEC-61000-4-5,Lever 3,IEC-61000-4-11,Criteria B
- Dimensions: (L)180*(W)180 *(H)13 mm
- Weight: 300g

Output Voltage	Load Regulation	Min Load	Rate Load	Max current
+V1(+24V)	±10%	0.1A	2.0A	2.5A
+V2(+12V)	±10%	0.1A	2.0A	3.0A
+V3(+5V)	±5%	0.1A	2.0A	3.0A
+V4(5VSB)	±5%	0.1A	0.5A	1.0A