

LCD Touch Monitor

FAD Series



Features :

- * 10.1" VGA 1280 x 800 LCD panel with LED backlight for power saving
- * 0°C ~ 50°C range operating temperature
- * Multi-touch PCT touchscreen with USB interface
- * Flexible signal interface: VGA, DVI, HDMI,
- * VESA mounting
- * True flat surface
- * 9~36V DC Power in

Model No : FAD-101PW-DN



Main Specifications

Display	Resolution	1280 x 800
	LCD Ratio	16:10
	Active Area (mm)	216.96 x 135.6 mm
	Pixels Pitch (mm)	0.1695 x 0.1695 mm
	Brightness (cd/m ²)	500 cd/m ²
	Contrast Ration	1300 : 1(Typ.)
	Response Time	30 ms
	Color Support	16.7M
	Viewing Angle	170° (H) / 170°(V)
	Back-light	LED
	Life Time	30000Hours
I/O Port	Input	VGA+DVI+HDMI+AUDIO
	Speakers (Optional)	2W+2W
Touch (Optional)	PANEL Type	Capacitive multi touch screen
	Structures	G+G
	Glass	3mm tempering glass
	Interface	USB
Power Consumption	Power Rating	DC 9~36V
	Max Power	<24W
Accessories	Standard	HDMI Cable. USB Cable
	Packing Box	Standard Shipping Box
	Operation Temp/Humidity	0~50°C , 20-90%RH
	Storage Temp/Humidity	-20~60°C , 10-90%RH

