

# LCD Touch Monitor

## FAD Series



### Features :

- \* 18.5" VGA 1920 x 1080 LCD panel with LED backlight for power saving
- \* 0°C ~ 50°C range operating temperature
- \* Multi-touch PCT touchscreen with USB interface
- \* Flexible signal interface: VGA, DVI, HDMI,
- \* VESA mounting
- \* True flat surface
- \* 9~36V DC Power in

Model No : FAD-185PW-DN



### Main Specifications

<b>Display</b>	Resolution	1920 x 1080
	LCD Ratio	16 : 9
	Active Area (mm)	408.96 x 230.04 mm
	Pixels Pitch (mm)	0.213 x 0.213 mm
	Brightness (cd/m <sup>2</sup> )	350 cd/m <sup>2</sup>
	Contrast Ration	1200 : 1(Typ.)
	Response Time	30 ms
	Color Support	16.7M
	Viewing Angle	178° (H) / 178°(V)
	Back-light	LED
	Life Time	30000Hours
<b>I/O Port</b>	Input	VGA+DVI+HDMI+AUDIO
	Speakers (Optional)	2W+2W
<b>Touch (Optional)</b>	PANEL Type	Capacitive multi touch screen
	Structures	G+G
	Glass	3mm tempering glass
	Interface	USB
<b>Power Consumption</b>	Power Rating	DC 9~36V
	Max Power	<36W
<b>Accessories</b>	Standard	HDMI Cable. USB Cable
	Packing Box	Standard Shipping Box
	Operation Temp/Humidity	0~50°C , 20-90%RH
	Storage Temp/Humidity	-20~60°C , 10-90%RH

