

LCD Touch Monitor

FAD Series



Features :

- * 50" 1920 x 1080 LCD panel with LED backlight for power saving
- * 0°C ~ 50°C range operating temperature
- * Multi-touch PCT touchscreen with USB interface
- * Flexible signal interface: VGA, DVI, HDMI,
- * VESA mounting
- * True flat surface
- * AC 110~220V 50/60hz

Model No : FAD-500PW-DN



Main Specifications

Display	Resolution	1920 x 1080
	LCD Ratio	16 : 9
	Active Area (mm)	1095.84 x 616.41 mm
	Pixels Pitch (mm)	0.28537 x 0.28537 mm
	Brightness (cd/m ²)	350 cd/m ²
	Contrast Ration	4000 : 1(Typ.)
	Response Time	9.5 ms
	Color Support	16.7M
	Viewing Angle	178° (H) / 178°(V)
	Back-light	LED
Life Time	30000Hours	
I/O Port	Input	VGA+DVI+HDMI+AUDIO
	Speakers (Optional)	5W+5W
Touch (Optional)	PANEL Type	Capacitive multi touch screen
	Structures	G+G
	Glass	3mm tempering glass
	Interface	USB
Power Consumption	Power Rating	AC 110-220V 50/60hz
	Max Power	<80W
Accessories	Standard	Power Cord. HDMI Cable. USB Cable
	Packing Box	Standard Shipping Box
	Operation Temp/Humidity	0~50°C , 20-90%RH
	Storage Temp/Humidity	-20~60°C , 10-90%RH

