

LCD Touch Monitor

FAD Series



Features :

- * 32" 1920 x 1080 LCD panel with LED backlight for power saving
- * 0°C ~ 50°C range operating temperature
- * Multi-touch PCT touchscreen with USB interface
- * Flexible signal interface: VGA, DVI, HDMI,
- * VESA mounting
- * True flat surface
- * AC 110~220V 50/60hz

Model No : FAD-320PW-DN



Main Specifications

Display	Resolution	1920 x 1080
	LCD Ratio	16 : 9
	Active Area (mm)	698.4 x 392.85 mm
	Pixels Pitch (mm)	0.36375 x 0.36375 mm
	Brightness (cd/m ²)	350 cd/m ²
	Contrast Ration	1200 : 1(Typ.)
	Response Time	8 ms
	Color Support	16.7M
	Viewing Angle	178° (H) / 178°(V)
	Back-light	LED
I/O Port	Life Time	30000Hours
	Input	VGA+DVI+HDMI+AUDIO
Touch (Optional)	Speakers (Optional)	5W+5W
	PANEL Type	Capacitive multi touch screen
	Structures	G+G
	Glass	3mm tempering glass
Power Consumption	Interface	USB
	Power Rating	AC 110-220V 50/60hz
Accessories	Max Power	<60W
	Stand	Power Cord. HDMI Cable. USB Cable
	Packing Box	Standard Shipping Box
	Operation Temp/Humidity	0~50°C , 20-90%RH
	Storage Temp/Humidity	-20~60°C , 10-90%RH

