

## LCD Open Frame Monitor



### Features :

- \* 17" VGA 1280 x 1024 LCD panel with LED backlight for power saving
- \* 0°C ~ 50°C range operating temperature
- \* Flexible signal interface: VGA, DVI, HDMI,
- \* VESA mounting
- \* True flat surface
- \* 9~36V DC Power in

Model No : OFD-170XN-VN



### Main Specifications

|                          |                                 |                       |
|--------------------------|---------------------------------|-----------------------|
| <b>Display</b>           | Resolution                      | 1280 x 1024           |
|                          | LCD Ratio                       | 5 : 4                 |
|                          | Active Area (mm)                | 337.92 x 270.336 mm   |
|                          | Pixels Pitch (mm)               | 0.264 x 0.264 mm      |
|                          | Brightness (cd/m <sup>2</sup> ) | 350 cd/m <sup>2</sup> |
|                          | Contrast Ration                 | 1000 : 1(Typ.)        |
|                          | Response Time                   | 5 ms                  |
|                          | Color Support                   | 16.7M                 |
|                          | Viewing Angle                   | 170° (H) / 160°(V)    |
|                          | Back-light                      | LED                   |
|                          | Life Time                       | 50000Hours            |
| <b>I/O Port</b>          | Input                           | VGA+DVI+HDMI+AUDIO    |
|                          | Speakers (Optional)             | 2W+2W                 |
| <b>Power Consumption</b> | Power Rating                    | DC 9~36V              |
|                          | Max Power                       | <36W                  |
| <b>Accessories</b>       | Stand                           | HDMI Cable            |
|                          | Packing Box                     | Standard Shipping Box |
|                          | Operation Temp/Humidity         | 0~50°C , 20-90%RH     |
|                          | Storage Temp/Humidity           | -20~60°C , 10-90%RH   |

